

MODEL 30-8



POWER CAVITY

- Brake: 6"
- Angle Shear
- Channel Shear
- Rod Shear (Round or Square)
- Z & T Shear

PUNCH STATION

- Coper Notcher
- Pipe Notcher

Throat Depth	4 1/2"
Tonnage	30
Punch	3/4" hole in 1/2" 1 1/4" hole in 5/16"
Bar Shear	1/4" X 8" 1/2" X 6"
Angle Shear 90° - Server Cut	3" X 3" X 1/4"
Miter Angle 45° - Bar Shear	2" X 2" standard
Channel Shear	1" X 2" standard
Rod Shear - Round (max) - Square (max)	5/8" 5/8"
Coper Notcher 90°	For 3" X 3" X 1/4" angle
Pipe Notcher Sched 40 or 80	1/2", 3/4", 1", 1 1/4", 1 1/2", 1 3/4", 2"
Brake	6" x 1/4"
Strokes per minute - light material - at max capacity	9
Hydraulics	1,000 psi
Oil Capacity	15 quarts
Motor - Standard - Optional	3 HP, 3 phase 3 HP, 1 phase
Dimensions - Width - Length - Height	24" 27" 50"
Weight (net)	880 lbs.

Accessories

- Punch nut wrench**
- Bar shear stop for production shearing to 24"**
- Grease bank for under cover lubrication**
- Punch Rack holds up to 30 sets of Punches & Dies**
- Steel bin catcher catches steel dropping from bar shear**
- Offset die stand for punching close to web ***

Please specify: size of angle to be punched, largest diameter hole to be punched and distance out from web to center of hole

Features

- 8" Bar Shear with 4 Sided bar blades**
- Fixed or Adjustable bar shear hold-down**
- Forklift accommodations**
- Magnetic starter for safety and reliability**
- Sits flush with wall freeing up floor space**
- Rated for 65,000 PSI Tensile Mild Steel**
- Better designed for safety and durability**

Tooling

- 6" Brake**
- Angle Shear**
- Channel Shear**
- Rod Shear**
- Coper Notcher**
- Pipe Notcher**

Uni-Hydro, Inc

310 E Gemini Ave
Cosmos, MN 56228
800 - 328 - 0036